

# PVCGRIP35



PVC GLOVE - LENGTH 35 CM Ref. PVCGRIP35





## Product specifications

PVC on cotton jersey lining, double-dipped. Length: 35 cm. Thickness 0,90 mm.

Support: jersey cotton. Coating: 100% PVC.

COLOUR

Green

SIZE

09, 10

#### Product Use - Risks



Wearing



Construction / Civil engineering



Heavy industry



Mining



Product's highlights & user's benefits					
	Knit cotton jersey gauge 10	Absorption of perspiration and moisture for improved comfort in everyday life			
	Textured structure	Good grip of handled objects			
	PVC	Good resistance to abrasion Material very resistant to oils, chemicals and petroleum derivatives			

#### Certifications and Standards



#### **REGULATION (EU) 2016/425**


#### EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

### EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)





- TYPE C: Type C Water and air tightness according to EN374-2:2014. Permeation resistance to at least 1 chemicals at level 1 according to EN16523-1: 2015 (from 1 to 6).
  - .: Determination of resistance to degradation by chemicals according to EN374-4: 2013. Part 4: Determination of resistance to degradation by chemicals.
  - K 6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2
  - N 2 > 30 mn: Acetic acid 99% (N) CAS 64-19-7



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.

BACTERIA + FUNGI : Water and air tightness according to EN374-2:2014.



References							
References	Bar code	COLOUR	SIZE	•	À		
PVCGRIP35VE09	3295249187712	Green	09	120	10		
PVCGRIP35VE10	3295249187729	Green	10	120	10		